

**BLACKFAST 833 DEWATERING OIL** 

Page: 1

Compilation date: 06/07/2012

Revision date: 21/03/2017

Revision No: 5

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: BLACKFAST 833 DEWATERING OIL

Product code: 833

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Use as supplied. PC14: Metal surface treatment products, including galvanic and

electroplating products. PC24: Lubricants, greases, release products. PC25: Metal working fluids. PROC4: Use in batch and other process (synthesis) where opportunity for exposure

arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to

vessels/large containers at non-dedicated facilities PROC13: Treatment of articles by dipping and pouring ERC5: Industrial use resulting in inclusion into or onto a matrix USES ADVISED

AGAINST: PROC7: Industrial spraying PROC11: Non industrial spraying

## 1.3. Details of the supplier of the safety data sheet

Company name: Blackfast Chemicals Ltd.

Unit 5 Russell House

Molesey Road

Walton-on-Thames

Surrey KT12 3PE

UK

Tel: +44 (0)208 339 7370

Fax: +44 (0)208 339 7371

Email: sales@blackfast.com

## 1.4. Emergency telephone number

Emergency tel: +44(0)1865 407333

# **Section 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304

Most important adverse effects: May be fatal if swallowed and enters airways.

#### 2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

Hazard pictograms: GHS08: Health hazard

**BLACKFAST 833 DEWATERING OIL** 

Page: 2



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P260: Do not breathe spray.

P262: Do not get in eyes, on skin, or on clothing.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P405: Store locked up.

#### 2.3. Other hazards

Other hazards: Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis.

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### **Hazardous ingredients:**

### LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-150-3	64742-48-9	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226	>75%

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY PARAFFINIC - REACH registered number(s): 01-2119488706-23-XXXX

265-090-8	64741-88-4	-	-	10-20%	
_00 000 0	0 00 .			.0 =0 /0	

# Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

**BLACKFAST 833 DEWATERING OIL** 

Page: 3

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up

to prevent the escape of liquid.

# 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Steel drums. Polyethylene.

## 7.3. Specific end use(s)

Specific end use(s): PC14: Metal surface treatment products, including galvanic and electroplating products.

PC24: Lubricants, greases, release products.

**BLACKFAST 833 DEWATERING OIL** 

Page: 4

### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

# **Hazardous ingredients:**

# LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

### Workplace exposure limits:

# Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	180	-	-	-

### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves. Nitrile gloves. Breakthrough time of the glove material > 8 hours.

Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

**Skin protection:** Protective clothing. Solvent resistant protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Oil

Colour: Brown

Odour: Solvent.

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: No data available.

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 67 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

**Relative density:** 0.82 **pH:** No data available.

VOC g/I: 645

### 9.2. Other information

Other information: No data available.

**BLACKFAST 833 DEWATERING OIL** 

Page: 5

# Section 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

### Relevant hazards for product:

Hazard	Route	Basis
Aspiration hazard	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## **Section 12: Ecological information**

## 12.1. Toxicity

Ecotoxicity values: No data available.

# 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

**BLACKFAST 833 DEWATERING OIL** 

Page: 6

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

### Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 13 08 99

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

### **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

### **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

# **Section 16: Other information**

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.